



02P35Z

POWER MOSFET

200mA, 350V P-CHANNEL POWER MOSFET



DESCRIPTION

The UTC **02P35Z** is a silicon P-channel MOSFET, it uses UTC's advanced technology to provide the customers with a minimum on state resistance, high switching speed and low gate charge.

FEATURES

- * $R_{DS(ON)} \leq 15\Omega$ @ $V_{GS}=-10V, I_D=-0.1A$
- $R_{DS(ON)} \leq 16.5\Omega$ @ $V_{GS}=-4.5V, I_D=-0.1A$
- * High switching speed
- * Low input capacitance

SYMBOL



SOT-23
(EIAJ SC-59)


ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
02P35ZL-AE3-R	02P35ZG-AE3-R	SOT-23	G	S	D	Tape Reel

Note: Pin Assignment: G: Gate S: Source D: Drain

02P35ZG-AE3-R	(1)Packing Type	(1) R: Tape Reel
	(2)Package Type	(2) AE3: SOT-23
	(3)Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free

MARKING



■ ABSOLUTE MAXIMUM RATING ($T_C=25^\circ\text{C}$ unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	-350	V
Gate-Source Voltage		V_{GSS}	± 20	V
Drain Current	DC	I_D	-0.2	A
	Pulsed (Note 2)	I_{DM}	-0.4	A
Power Dissipation		P_D	0.3	W
Junction Temperature		T_J	+150	$^\circ\text{C}$
Storage Temperature Range		T_{STG}	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating : Pulse width limited by maximum junction temperature.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	350	$^\circ\text{C/W}$


■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	$V_{GS}=0V, I_D=-250\mu\text{A}$	-350			V
Drain-Source Leakage Current		I_{DSS}	$V_{DS}=-350V, V_{GS}=0V$			-10	μA
Gate-Source Leakage Current	Forward	I_{GSS}	$V_{GS}=+20V, V_{DS}=0V$			+10	μA
	Reverse		$V_{GS}=-20V, V_{DS}=0V$			-10	μA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=-250\mu\text{A}$	-1.0		-2.5	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	$V_{GS}=-10V, I_D=-0.1A$			15	Ω
			$V_{GS}=-4.5V, I_D=-0.1A$			16.5	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C_{ISS}	$V_{GS}=0V, V_{DS}=-25V, f=1.0\text{MHz}$		77		pF
Output Capacitance		C_{OSS}			17.7		pF
Reverse Transfer Capacitance		C_{RSS}			4		pF
SWITCHING PARAMETERS							
Total Gate Charge		Q_G	$V_{DS}=-280V, V_{GS}=-10V, I_D=-200\text{mA}, I_G=-1\text{mA}$ (Note 1, 2)		8.4		nC
Gate to Source Charge		Q_{GS}			1.92		nC
Gate to Drain Charge		Q_{GD}			0.9		nC
Turn-ON Delay Time		$t_{D(ON)}$	$V_{DD}=-100V, V_{GS}=-10V, I_D=-200\text{mA}, R_G=25\Omega$ (Note 1, 2)		3.2		ns
Rise Time		t_R			17.3		ns
Turn-OFF Delay Time		$t_{D(OFF)}$			22.4		ns
Fall-Time		t_F			43.9		ns
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Continuous Drain-Source Diode Forward Current		I_S				-1	A
Maximum Pulsed Drain-Source Diode Forward Current		I_{SM}				-2	A
Diode Forward Voltage		V_{SD}	$I_F=-0.2A, V_{GS}=0V$			-1.4	V


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Gate Charge Test Circuit




Gate Charge Waveforms




Resistive Switching Test Circuit



Resistive Switching Waveforms









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.