



## 2SK2751

N-CHANNEL JFET


### N-CHANNEL JUNCTION FET

#### FEATURES

- \* Low noise-figure (NF).
- \* High gate to drain voltage  $V_{GD0}$ .

#### APPLICATIONS

- \* For impedance conversion in low frequency.
- \* For pyroelectric sensor.




#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
2SK2751L-AE3-R	2SK2751G-AE3-R	SOT-23	S	D	G	Tape Reel
2SK2751L-AL3-R	2SK2751G-AL3-R	SOT-323	S	D	G	Tape Reel

Note: Pin Assignment: S: Source D: Drain G: Gate

<p>2SK2751G-AE3-R</p> <p>(1) Packing Type (2) Package Type (3) Green Package</p>	<p>(1) R: Tape Reel (2) AE3: SOT-23, AL3: SOT-323 (3) G: Halogen Free and Lead Free, L: Lead Free</p>
--	---

#### MARKING



■ **ABSOLUTE MAXIMUM RATINGS** ( $T_A=25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Gate-Drain Voltage	$V_{GDS}$	-40	V
Drain Current	$I_D$	10	mA
Gate Current	$I_G$	2	mA
Allowable Power Dissipation	$P_D$	200	mW
Channel Temperature	$T_{CH}$	+150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-55 ~ +150	$^\circ\text{C}$






Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ **ELECTRICAL CHARACTERISTICS** ( $T_A=25\pm 3^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Gate-Drain Voltage	$V_{GDS}$	$I_G=-100\mu\text{A}$ , $V_{DS}=0$	-40			V
Gate-Source Cut-Off Voltage	$V_{GSC}$	$V_{DS}=10\text{V}$ , $I_D=1\mu\text{A}$			-3.5	V
Drain-Source Cut-Off Current	$I_{DSS}$	$V_{DS}=10\text{V}$ , $V_{GS}=0$	1.4		4.7	mA
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS}=-20\text{V}$ , $V_{DS}=0$			-1	nA
Forward Transfer Admittance	$ Y_{fs} $	$V_{DS}=10\text{V}$ , $V_{GS}=0$ , $f=1\text{kHz}$	2.5			mS
Input Capacitance (Common Source)	$C_{ISS}$	$V_{DS}=10\text{V}$ , $V_{GS}=0$ , $f=1\text{MHz}$		5		pF
Output Capacitance (Common Source)	$C_{OSS}$			1		pF
Reverse Transfer Capacitance (Common Source)	$C_{RSS}$			1		pF

## TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.