



U74AHC02

CMOS IC


2-INPUT NOR GATE

DESCRIPTION

The UTC **U74AHC02** are independent 2-input NOR gates which provides the function $Y = \overline{A+B}$.

FEATURES

- * Operation Voltage Range: 2.0~5.5V
- * Low Power Dissipation
- * High Noise Immunity
- * Balanced Propagation Delays




ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
U74AHC02L-S14-R	U74AHC02G-S14-R	SOP-14	Tape Reel
U74AHC02L-S14-T	U74AHC02G-S14-T	SOP-14	Tube
U74AHC02L-P14-R	U74AHC02G-P14-R	TSSOP-14	Tape Reel
U74AHC02L-P14-T	U74AHC02G-P14-T	TSSOP-14	Tube

<p>U74AHC02L-S14-R</p> <p>(1) Packing Type (2) Package Type (3) Lead Free</p>	<p>(1) R: Tape Reel, T: Tube (2) S14: SOP-14, P14: TSSOP-14 (3) G: Halogen Free, L: Lead Free</p>
---	---

■ PIN CONFIGURATION



■ FUNCTION TABLE

INPUT		OUTPUT
A	B	Y
L	L	H
L	H	L
H	L	L
H	H	L

■ LOGIC DIAGRAM (positive logic)



IEC logic symbol

■ ABSOLUTE MAXIMUM RATINGS (unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V_{CC}	-0.5~+7	V
Input Voltage	V_{IN}	-0.5~+7	V
Output Voltage	V_{OUT}	-0.5~ $V_{CC}+0.5$	V
Input Clamp Current	I_{IK}	-20	mA
Output Clamp Current	I_{OK}	± 20	mA
Continuous Output Current	I_{OUT}	± 25	mA
V_{CC} or GND Current	I_{CC}	± 50	mA
Storage Temperature	T_{STG}	-65 ~ + 150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}		2		5.5	V
Input Voltage	V_{IN}		0		5.5	V
Output Voltage	V_{OUT}	High or low state	0		V_{CC}	V
Input Voltage	High	V_{IH}	$V_{CC}=2V$	1.5		V
			$V_{CC}=3V$	2.1		V
			$V_{CC}=5.5V$	3.85		V
	Low	V_{IL}	$V_{CC}=2V$		0.5	V
			$V_{CC}=3V$		0.9	V
			$V_{CC}=5.5V$		1.65	V
Output Current	High	I_{OH}	$V_{CC}=2V$		-50	μA
			$V_{CC}=3.3V \pm 0.3V$		-4	mA
			$V_{CC}=5V \pm 0.5V$		-8	mA
	Low	I_{OL}	$V_{CC}=2V$		50	μA
			$V_{CC}=3.3V \pm 0.3V$		4	mA
			$V_{CC}=5V \pm 0.5V$		8	mA
Input Rise or Fall Times	$\frac{\Delta t}{\Delta V}$	$V_{CC}=3.3V \pm 0.3V$			100	ns/V
		$V_{CC}=5V \pm 0.5V$			20	ns/V
Operating Temperature	T_{OPR}		-40		125	°C

■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ C$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT	
Output Voltage	High	V_{OH}	$V_{CC}=2.0V, I_{OH}=-50\mu A$	1.9	2.0		V
			$V_{CC}=3.0V, I_{OH}=-50\mu A$	2.9	3.0		V
			$V_{CC}=4.5V, I_{OH}=-50\mu A$	4.4	4.5		V
			$V_{CC}=3.0V, I_{OH}=-4mA$	2.58			V
			$V_{CC}=4.5V, I_{OH}=-8mA$	3.94			V
	Low	V_{OL}	$V_{CC}=2.0V, I_{OL}=50\mu A$			0.1	V
			$V_{CC}=3.0V, I_{OL}=50\mu A$			0.1	V
			$V_{CC}=4.5V, I_{OL}=50\mu A$			0.1	V
			$V_{CC}=3.0V, I_{OL}=4mA$			0.36	V
			$V_{CC}=4.5V, I_{OL}=8mA$			0.36	V
Input Leakage Current	$I_{I(LEAK)}$	$V_{CC}=0\sim 5.5V, V_{IN}=5.5V$ or GND			± 0.1	μA	
Quiescent Supply Current	I_Q	$V_{CC}=5.5V, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$			2	μA	
Input Capacitance	C_{IN}	$V_{CC}=5.0V, V_{IN}=V_{CC}$ or GND		4	10	pF	

Note: All unused inputs of the device must be held at V_{CC} or GND to ensure proper device operation.


■ SWITCHING CHARACTERISTICS (see Test Circuit and Waveforms)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from input (A or B) to output(Y)	t_{PLH}/t_{PHL}	$V_{CC}=3.3V\pm 0.3V, C_L=15pF$		5.6	7.9	ns
		$V_{CC}=3.3V\pm 0.3V, C_L=50pF$		8.1	11.4	ns
	t_{PLH}/t_{PHL}	$V_{CC}=5.0V\pm 0.5V, C_L=15pF$		3.6	5.5	ns
		$V_{CC}=5.0V\pm 0.5V, C_L=50pF$		5.1	7.5	ns


■ OPERATING CHARACTERISTICS ($V_{CC}=5V, T_a=25^\circ C$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	C_{PD}	No load, $f=1MHz$		15		pF


■ TEST CIRCUIT AND WAVEFORMS



TEST	S
t _{PLH} /t _{PHL}	Open
t _{PHZ} /t _{PZH}	GND
t _{PLZ} /t _{PZL}	V _{CC}



SETUP TIME AND HOLD TIME



PROPAGATION DELAY TIMES

Note: C_L includes probe and jig capacitance.

P_{RR} ≤ 1MHz, Z_O = 50Ω, t_r ≤ 3ns, t_f ≤ 3ns.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.