

78DXXA

LINEAR INTEGRATED CIRCUIT


3-TERMINALS 1A POSITIVE VOLTAGE REGULATOR

DESCRIPTION

The UTC **78DXXA** family is monolithic fixed voltage regulator integrated circuit. They are suitable for applications that required supply current up to 1 A.

FEATURES

- * Peak output current up to 1A.
- * Fixed output voltage of 5V, 6V, 7V, 8V, 9V, 10V, 12V, 15V, 18V, 20V and 24V available.
- * Thermal overload shutdown protection.
- * Short circuit current limiting.
- * Output transistor SOA protection.



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment								Packing
Lead Free	Halogen Free		1	2	3	4	5	6	7	8	
78DXXAL-AA3-R	78DXXAG-AA3-R	SOT-223	I	G	O	-	-	-	-	-	Tape Reel
78DXXAL-TM3-T	78DXXAG-TM3-T	TO-251	I	G	O	-	-	-	-	-	Tube
78DXXAL-TN3-R	78DXXAG-TN3-R	TO-252	I	G	O	-	-	-	-	-	Tape Reel
78DXXAL-TNA-R	78DXXAG-TNA-R	TO-252-3	I	G	O	-	-	-	-	-	Tape Reel
78DXXAL-S08-R	78DXXAG-S08-R	SOP-8	O	G	G	N	N	G	G	I	Tape Reel


Note: Pin Code: I: Input G: GND O: Output

78DXXAG-AA3-R	(1)Packing Type	(1) R: Tape Reel, T: Tube
	(2)Package Type	(2) AA3: SOT-223, TM3: TO-251, TN3: TO-252, TNA: TO-252-3, S08: SOP-8
	(3)Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free
	(4)Output Voltage Code	(4) XX: refer to Marking Information


■ MARKING INFORMATION

PACKAGE	VOLTAGE CODE	MARKING
SOT-223	05: 5V 06: 6V 07: 7V 08: 8V 09: 9V 10: 10V 12: 12V 15: 15V 18: 18V 20: 20V 24: 24V	
TO-251 TO-252 TO-252-3		
SOP-8		

■ BLOCK DIAGRAM



■ APPLICATION CIRCUIT



Note: Bypass capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators.

■ ABSOLUTE MAXIMUM RATINGS (T_A = 25°C, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Input Voltage	V _{OUT} =5~20V	V _{IN}	35	V
	V _{OUT} =24V		40	V
Output Current		I _{OUT}	1	A
Power Dissipation (T _C =25°C)	SOT-223	P _D	606	mW
	TO-251/TO-252		890	mW
	TO-252-3			
	SOP-8		666	mW
Junction Temperature		T _J	+150	°C
Operating Temperature		T _{OPR}	-40 ~ +125	°C
Storage Temperature		T _{STG}	-55 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	SOT-223	θ _{JA}	165	°C/W
	TO-251/TO-252		112	°C/W
	TO-252-3			
	SOP-8		150	°C/W
Junction to Case	SOT-223	θ _{JC}	15	°C/W
	TO-251/TO-252		12	°C/W
	TO-252-3			
	SOP-8		20	°C/W

■ ELECTRICAL CHARACTERISTICS

(T_J=25°C, C_I=0.33μF, C_O=0.1μF, P_D≤15W, unless otherwise specified)

For 78D05A (V_{IN}=10V, I_{OUT}=1.0A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V _{OUT}	I _{OUT} = 5mA~1.0A	4.90	5.0	5.10	V
		V _{IN} = 7.5~20V, I _{OUT} = 5mA~1.0A	4.85		5.15	V
Load Regulation	ΔV _{OUT}	I _{OUT} = 5mA~1.0A			50	mV
		I _{OUT} = 0.25A~0.75A			25	mV
Line Regulation	ΔV _{OUT}	V _{IN} = 7~25V			50	mV
		V _{IN} = 7.5~20V, I _{OUT} = 1.0A			50	mV
Quiescent Current	I _Q	I _{OUT} ≤ 1.0A			8.0	mA
Quiescent Current Change	ΔI _Q	V _{IN} = 7.5~20V			1.0	mA
		I _{OUT} = 5mA~1.0A			0.5	mA
Output Noise Voltage	e _N	10Hz ≤ f ≤ 100kHz		40		μV
Ripple Rejection	RR	V _{IN} = 8~18V, f = 120Hz	59	80		dB
Peak Output Current	I _{PEAK}			1.8		A
Short-Circuit Current	I _{SC}	V _{IN} = 35V		250		mA
Dropout Voltage	V _D			2.0		V

■ ELECTRICAL CHARACTERISTICS (Cont.)

For 78D06A ($V_{IN}=11V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	5.88	6.0	6.12	V
		$V_{IN}=8.5\sim21V$, $I_{OUT}=5mA\sim1.0A$	5.82		6.18	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			60	mV
		$I_{OUT}=0.25A\sim0.75A$			30	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=8\sim25V$			60	mV
		$V_{IN}=8.5\sim21V$, $I_{OUT}=1.0A$			60	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=8.5\sim21V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		45		μV
Ripple Rejection	RR	$V_{IN}=9\sim19V$, $f=120Hz$	56	75		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

For 78D07A ($V_{IN}=13V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	6.86	7.0	7.14	V
		$V_{IN}=9.5\sim22V$, $I_{OUT}=5mA\sim1.0A$	6.79		7.21	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			70	mV
		$I_{OUT}=0.25A\sim0.75A$			35	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=9\sim25V$			70	mV
		$V_{IN}=9.5\sim22V$, $I_{OUT}=1.0A$			70	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=9.5\sim22V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		50		μV
Ripple Rejection	RR	$V_{IN}=10.5V\sim20.5V$, $f=120Hz$	56	75		dB
Peak Output Current	I_{PEAK}			1.7		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

For 78D08A ($V_{IN}=14V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	7.84	8.0	8.16	V
		$V_{IN}=10.5\sim23V$, $I_{OUT}=5mA\sim1.0A$	7.76		8.24	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			80	mV
		$I_{OUT}=0.25A\sim0.75A$			40	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=10.5\sim25V$			80	mV
		$V_{IN}=10.5\sim23V$, $I_{OUT}=1.0A$			80	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=10.5\sim23V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		58		μV
Ripple Rejection	RR	$V_{IN}=11.5\sim21.5V$, $f=120Hz$	53	72		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

■ ELECTRICAL CHARACTERISTICS (Cont.)

For 78D09A ($V_{IN}=15V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	8.82	9.0	9.18	V
		$V_{IN}=11.5\sim24V$, $I_{OUT}=5mA\sim1.0A$	8.73		9.27	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			90	mV
		$I_{OUT}=0.25A\sim0.75A$			45	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=11.5\sim25V$			90	mV
		$V_{IN}=11.5\sim24V$, $I_{OUT}=1.0A$			90	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=11.5\sim24V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		58		μV
Ripple Rejection	RR	$V_{IN}=12.5\sim22.5V$, $f=120Hz$	53	72		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

For 78D10A ($V_{IN}=16V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	9.8	10	10.2	V
		$V_{IN}=12.5\sim25V$, $I_{OUT}=5mA\sim1.0A$	9.7		10.3	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			100	mV
		$I_{OUT}=0.25A\sim0.75A$			50	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=13\sim25V$			100	mV
		$V_{IN}=13\sim25V$, $I_{OUT}=1.0A$			100	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=12.6V\sim25V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		58		μV
Ripple Rejection	RR	$V_{IN}=13\sim23V$, $f=120Hz$	53	72		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

For 78D12A ($V_{IN}=19V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	11.76	12	12.24	V
		$V_{IN}=14.5\sim27V$, $I_{OUT}=5mA\sim1.0A$	11.64		12.36	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			120	mV
		$I_{OUT}=0.25A\sim0.75A$			60	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=14.5\sim30V$			120	mV
		$V_{IN}=14.6\sim27V$, $I_{OUT}=1.0A$			120	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=14.5\sim30V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		75		μV
Ripple Rejection	RR	$V_{IN}=15\sim25V$, $f=120Hz$	52	72		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

■ ELECTRICAL CHARACTERISTICS (Cont.)

For 78D15A ($V_{IN}=23V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	14.70	15	15.30	V
		$V_{IN}=17.5\sim30V$, $I_{OUT}=5mA\sim1.0A$	14.55		15.45	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			150	mV
		$I_{OUT}=0.25A\sim0.75A$			75	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=18.5\sim30V$			150	mV
		$V_{IN}=17.7\sim30V$, $I_{OUT}=1.0A$			150	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=17.5\sim30V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		90		μV
Ripple Rejection	RR	$V_{IN}=18.5\sim28.5V$, $f=120Hz$	51	70		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

For 78D18A ($V_{IN}=27V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	17.64	18	18.36	V
		$V_{IN}=21\sim33V$, $I_{OUT}=5mA\sim1.0A$	17.46		18.54	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			180	mV
		$I_{OUT}=0.25A\sim0.75A$			90	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=21\sim33V$			180	mV
		$V_{IN}=21\sim33V$, $I_{OUT}=1.0A$			180	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=21.5\sim33V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		110		μV
Ripple Rejection	RR	$V_{IN}=22\sim32V$, $f=120Hz$	50	69		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

For 78D20A ($V_{IN}=29V$, $I_{OUT}=1.0A$)







PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	19.6	20	20.4	V
		$V_{IN}=23\sim35V$, $I_{OUT}=5mA\sim1.0A$	19.4		20.6	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			200	mV
		$I_{OUT}=0.25A\sim0.75A$			100	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=23\sim35V$			200	mV
		$V_{IN}=23\sim35V$, $I_{OUT}=1.0A$			200	mV
Quiescent Current	I_Q	$I_{OUT}\leq1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=23.5\sim35V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		130		μV
Ripple Rejection	RR	$V_{IN}=24\sim34V$, $f=120Hz$	49	68		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

■ ELECTRICAL CHARACTERISTICS (Cont.)

For 78D24A ($V_{IN}=33V$, $I_{OUT}=1.0A$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$I_{OUT}=5mA\sim1.0A$	23.52	24	24.48	V
		$V_{IN}=27\sim38V$, $I_{OUT}=5mA\sim1.0A$	23.28		24.72	V
Load Regulation	ΔV_{OUT}	$I_{OUT}=5mA\sim1.0A$			240	mV
		$I_{OUT}=0.25A\sim0.75A$			120	mV
Line Regulation	ΔV_{OUT}	$V_{IN}=27\sim38V$			240	mV
		$V_{IN}=27\sim38V$, $I_{OUT}=1.0A$			240	mV
Quiescent Current	I_Q	$I_{OUT}\leq 1.0A$			8.0	mA
Quiescent Current Change	ΔI_Q	$V_{IN}=28\sim38V$			1.0	mA
		$I_{OUT}=5mA\sim1.0A$			0.5	mA
Output Noise Voltage	eN	$10Hz\leq f\leq 100kHz$		170		μV
Ripple Rejection	RR	$V_{IN}=28\sim38V$, $f=120Hz$	47	66		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	$V_{IN}=35V$		250		mA
Dropout Voltage	V_D			2.0		V

TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.